

1 7/16" Cable Head Assembly

Description

Cable Heads are used in all logging and perforating operations as they provide mechanical and electrical connections between the cable and tool string. Variety hole sizes of fishing neck is available for differing cable diameters.

This component is designed and manufactured based on high pressure and high temperature operational conditions and is capable to be used several times.

Specification

| | |
|---------------------------|--------------------------------------|
| <i>Part Number</i> | <i>Depend on Cable Specification</i> |
| <i>Diameter</i> | <i>1.44 in (36.5mm)</i> |
| <i>Length</i> | <i>17.5 in (445 mm)</i> |
| <i>Pressure Rating</i> | <i>20,000 psi</i> |
| <i>Temperature Rating</i> | <i>Depending on O-Ring</i> |
| <i>Thread Type</i> | <i>1 3/16"- 12 UN -2A</i> |

O-Ring Specification

| | |
|---------------------------|----------------------|
| <i>Part Number</i> | <i>ORV-211</i> |
| <i>Temperature Rating</i> | <i>400 °F(204°C)</i> |
| <i>Required No.</i> | <i>2 Pcs</i> |

Packing Information

| | |
|----------------------|-------------------|
| <i>Package (pcs)</i> | <i>--</i> |
| <i>Package Type</i> | <i>Wooden Box</i> |

Note: Packing specification is set based on customer request

